



Lexmark CS735de

Colour made easy















Lexmark CS735de

Designed for security, ease of use, and sustainability, the Lexmark CS735de delivers professional colour for mid-to-large workgroups at speeds up to 50 pages per minute*. The 10.9 cm tablet-like touchscreen makes completing your printing tasks intuitively easy. Replacement cartridges with Unison™ Toner yield up to 22,000/12,500 black/colour pages** to keep you going.

Make a statement with professional colour

Enjoy the benefits of vibrant, professional-quality output allowing you to do more colour printing in-house - saves time and money. Match corporate colours on marketing collateral and brand-sensitive text and graphics with PANTONE® calibration and Lexmark Named Colour Replacement.

Made to last. Easy to upgrade.

- With durable steel frames, long-life components and highyield cartridges, printers are intentionally engineered to last seven years or more.
- Long-lasting Unison™ Toner delivers consistently outstanding print quality, reduces internal wear on longlife components, and protects the print system.
- Easily upgradeable to the latest apps and security features.



Always easy. Always intuitive.

Powerful features are easy to use.

- Large, tablet-like, button-free touchscreens help you intuitively complete every task, from the basic to the complex.
- Add Lexmark or third-party apps to meet your specific business needs.

Secure by design

- Lexmark security features help keep your information safe

 in the document, on the device, over the network and at
 all points in between.
- Always improving security, we now include a standard Trusted Platform Module***, which delivers authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint.

Sustainability matters

- Designed for the circular economy.
- Automatic two-sided printing is standard, along with builtin energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- The award-winning Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

Power up with IoT

- Sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- When you connect your device to Lexmark Cloud Services, you can optimise performance and uptime with additional features like predictive service and automatic supplies replenishment.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

^{*} Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

^{**} Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

^{***} The Trusted Platform Module (TPM) is not available in some countries.

Lexmark CS735de



- 1 Printer with 10.9 cm touch screen 413 x 479 x 489 mm
- 550-Sheet tray with 100-sheet 2 multipurpose feeder Dimensions included as part of base model
- 550-Sheet Drawer (incl. Tray) 3 119 x 463 x 483 mm
- 550-Sheet Drawer (incl. Tray) 4 119 x 463 x 483 mm
- 5 550-Sheet Drawer (incl. Tray) 119 x 463 x 483 mm
- 550-Sheet Drawer (incl. Tray) 6 119 x 463 x 483 mm
- Printer Stand (adjustable height)



Standard



Optional

P/N Hardware 47C9120 Lexmark CS735de P/N **Supplies** 71C0H10 Lexmark CS730, 735, CX730 Black 22K Toner Cartridge Lexmark CS/CX730, 735, C/ XC4342, C4352 170K Waste 71C0W00 Container 71C0X20 Lexmark CS735 Cyan 12.5K Toner Cartridge 71C0X30 Lexmark CS735 Magenta 12.5K Toner Cartridge Lexmark CS735 Yellow 12.5K 71C0X40 Toner Cartridge Lexmark CS/CX730, 735, C/ 71C0Z10 XC4342, C/XC4352 Black 150K **Imaging Unit** Lexmark CS/CX730, 735, C/ 71C0Z50 XC4342, C/XC4352 Colour (CMY) 150K Imaging Unit 71C20C0 Lexmark CS/CX730, 735 Cyan Return Programme 5K Toner Cartridge 71C20K0 Lexmark CS/CX730, 735 Black Return Programme 5K Toner Cartridge Lexmark CS/CX730, 735 71C20M0 Magenta Return Programme 5K Toner Cartridge Lexmark CS/CX730, 735 Yellow 71C20Y0 Return Programme 5K Toner Cartridge 71C2HK0 Lexmark CS730, 735, CX730 Black Return Programme 22K Toner Cartridge 71C2XC0 Lexmark CS735 Cyan Return Programme 12.5K Toner Cartridge Lexmark CS735 Magenta Return 71C2XM0 Programme 12.5K Toner Cartridge 71C2XY0 Lexmark CS735 Yellow Return Programme 12.5K Toner Cartridge P/N **Paper Handling** CS72x, CX725 550-Sheet Drawer 40C2100 (incl. Tray) P/N **Memory Options** 500+ GB Hard Disk 27X0400 57X9528 Intelligent Storage Drive (ISD) P/N **Application Solutions** 57X0300 Contact Authentication Device Contactless Authentication 57X0301 Device 82S1203 **IPDS** License Bar Code License 82S1204 P/N Connectivity 1021294 USB Cable (2 meter) 27X0823 MarkNet N8370 Wireless for CS720, CS725, CX725 27X6410 Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server

SPD0002

CS72x, CX725 Printer Stand

(adjustable height)

Surge protective device

Product Specifications	Lexmark CS735de
Printing	
Display	Lexmark e-Task 10,9 cm colour touch screen with audible feedback
Print speed	up to: black: 50 ppm ¹ (A4) / colour: 50 ppm ¹ (A4)
Time to first page	as fast as: black: 5.6 seconds / colour: 6.1 seconds
Print resolution	black: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi) / colour: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi
Memory	standard: 1024 MB / maximum: 1024 MB
Hard Disk	Intelligent Storage Drive available; Magnetic Hard Disk available
Recommended monthly page volume	2000 - 20000 pages ²
Maximum monthly duty cycle	up to: 150000 pages per month ³
Supplies ⁴	
Cartridge yields	up to: 12,500 ⁵ -page Colour (CMY) Extra High Yield Cartridges / up to: 22,000 ⁵ -page Black High Yield Cartridge
Imaging unit yield	up to: 150000 pages, based on average 3 pages per print job and 5% coverage ⁶
Cartridge(s) shipped with product	5,000 ⁵ -page Black and Colour (CMYK) Return Programme Toner Cartridges ⁵
Paper Handling	
Standard paper handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 300-sheet output bin, 550-Sheet Input
Optional paper handling	550-Sheet Tray
Paper input capacity	up to: standard: 650 pages / maximum: 2850 pages
Paper output capacity	up to: standard: 300 pages / maximum: 300 pages
Media types supported	Vinyl Labels, Banner Paper, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide
Media sizes supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope
General Information ⁷	
Standard connectivity	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port (compatible with USB 2.0 specification, type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot
Optional network ports	Internal MarkNet N8370 802.11b/g/n/a Wireless, NFC
Noise Level	Operating: 53 dBA (Print)
Specified operating environment	Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Metres (9,500 Feet) / Humidity: 15 to 80% Relative Humidity
Product guarantee	1-Year Onsite Service, Next Business Day
Size / Weight	HxWxD: 413 x 479 x 489 mm / 32 kg
Energy Star Typical Electricity Consumption	TEC: 0.65 kWh per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo, and the Mopria Alliance TM word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http://www.openssl.org/).



¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ⁶ Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁷ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.